INTRODUCING the NEW ASRCD MKII from MEMIE A'ASIA Pty Ltd

2 MODELS AVAILABLE

BOTH MODELS: BASIC and DATA STORAGE

- **Tests 10mA and 30mA RCDs.**
- **Minimum Tripping current from zero ramp.**
- **Tripping Time tests can be set Random, 0º or 180º.**
- **Manual or Auto mode testing. Auto test can be any combination up to a maximum of six tests.**
- **Minimum Tripping Current and 6 Tripping Time tests all on the screen.**
- **Coloured 3.4" Touch Screen. (No switches to wear out.)**
- **Rechargeable NiMh batteries. (No 9V battery to replace.)**

DATA STORAGE Model

- **Saves over 500 records**
- **Review Records**
- **Enter Data from Screen Keypad or optional inbuilt Barcode Reader.**
- **BLUETOOTH© Communication to Computer or other devices.**

GENERAL SPECIFICATIONS	
POWER SUPPLY REQUIREMENTS	
Voltage & Frequency	230-240V 50Hz
Power	8 VA Max
MANUFACTURING STANDARDS	Manufactured to AS3100
AMBIENT OPERATING TEMPERATURE	0 – 40ºC
ASRCD MKII DIMENSIONS	
Width	105 mm
Length	195 mm
Height	40 mm
TRANSPORT CASE DIMENSIONS	
Width	265 mm
Length	240 mm
Height	240 mm
WEIGHT	
Unpacked	0.478 kilograms
Packed	1.81 kg (including transport case)

MEMIE A'ASIA Pty Ltd

17 Daniel Court

WARRANWOOD VIC 3134

Ph: +61 3 98762298 Email: kob@mem.com.au www.mem.com.au